



SIPLUS LOGO! POWER 24V 2.5 A

SIPLUS LOGO! power 24 V 2.5 A based on 6EP3332-6SB00-0AY0 with conformal coating, -40...+70 °C, start up -25 °C, stabilized power supply input: 100-240 V AC output: 24 V DC/ 2.5 A

Input	
type of the power supply network	1-phase AC or DC
supply voltage at AC	
• minimum rated value	100 V
• maximum rated value	240 V
• initial value	85 V
• full-scale value	264 V
input voltage	
• at DC	110 ... 300 V
design of input wide range input	Yes
operating condition of the mains buffering	at Vin = 187 V
buffering time for rated value of the output current in the event of power failure minimum	40 ms
operating condition of the mains buffering	at Vin = 187 V
line frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	1.22 A
• at rated input voltage 230 V	0.66 A
current limitation of inrush current at 25 °C maximum	52 A
I2t value maximum	3 A²·s
fuse protection type	internal
• in the feeder	Recommended miniature circuit breaker: from 10 A characteristic B or from 6 A characteristic C
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	0.1 %
residual ripple	
• maximum	200 mV
• typical	30 mV
voltage peak	
• maximum	300 mV
• typical	50 mV
adjustable output voltage	22.2 ... 26.4 V

product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer
display version for normal operation	Green LED for output voltage OK
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	0.5 s
voltage increase time of the output voltage	
• typical	100 ms
output current	
• rated value	2.5 A
• rated range	0 ... 2.5 A; +55 ... +70 °C: Derating 2%/K
supplied active power typical	60 W
product feature	
• bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	90 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	7 W
• during no-load operation maximum	0.3 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.2 %
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	2 %
setting time	
• load step 10 to 90% typical	1 ms
• load step 90 to 10% typical	1 ms
Protection and monitoring	
design of the overvoltage protection	Yes, according to EN 60950-1
response value current limitation typical	3.2 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
• maximum	3.2 A
overcurrent overload capability in normal operation	overload capability 150% Iout rated typ. 200 ms
display version for overload and short circuit	-
measuring point for output current	50 mV = ^ 2.5 A
overcurrent overload capability when switching on	150% Iout rated typ. 200 ms
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class II (without protective conductor)
protection class IP	IP20
Approvals	
certificate of suitability	
• CE marking	Yes
EMC	
standard	
• for emitted interference	EN 55022 Class B
• for mains harmonics limitation	not applicable
• for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
• in horizontal mounting position during operation	-40; Startup @ -25 °C ... +70 °C; with natural convection
• during storage and transport	-40 ... +85 °C
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation according to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation

chemical resistance to commercially available cooling lubricants

resistance to biologically active substances conformity according to EN 60721-3-3

resistance to chemically active substances conformity according to EN 60721-3-3

resistance to mechanically active substances conformity according to EN 60721-3-3

resistance to biologically active substances conformity according to EN 60721-3-6

resistance to chemically active substances conformity according to EN 60721-3-6

resistance to mechanically active substances conformity according to EN 60721-3-6

coating for equipped printed circuit board according to EN 61086

type of coating protection against pollution according to EN 60664-3

type of test of the coating according to MIL-I-46058C

product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; incl. diesel and oil droplets in the air

Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request

Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)

Yes; Class 3S4 incl. sand, dust

Yes; Class 6B2 mold, fungal, sponge spores (except fauna)

Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)

Yes; Class 6S3 incl. sand, dust

Yes; Class 2 for high availability

Yes; Type 1 protection

Yes; Discoloration of the coating during service life possible

Yes; Conformal Coating, Class A

Mechanics

type of electrical connection

- at input
- at output
- for auxiliary contacts

width of the enclosure

height of the enclosure

depth of the enclosure

required spacing

- top
- bottom
- left
- right

net weight

product feature of the enclosure housing can be lined up

fastening method

MTBF at 40 °C

other information

screw-type terminals

L, N: 1 screw terminal each for 0.5 ... 2.5 mm² single-core/finely stranded

+, -: 2 screw terminals each for 0.5 ... 2.5 mm²

-

54 mm

90 mm

53 mm

20 mm

20 mm

0 mm

0 mm

0.2 kg

Yes

Snaps onto DIN rail EN 60715 35x7.5/15, direct mounting in different mounting positions

2 864 520 h

Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

