



SIMATIC ET 200SP, PROFINET interface module IM 155-6PN Standard, max. 32 I/O modules, and 16 ET 200AL modules, single hot swap, incl. server module (6ES7193-6PA00-0AA0)

| General information  |  |
|--|--|
| Product type designation   | IM 155-6 PN ST                                   |
| HW functional status   | From FS03  |
| Firmware version   | V4.2   |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>                                     | Yes  |
| Product function   |  |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3                                |
| <ul style="list-style-type: none"> <li>Module swapping during operation (hot swapping)</li> </ul>        | Yes; Single hot swapping                         |
| <ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>                                       | No   |
| Engineering with   |  |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | V14  |
| <ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>            | V5.5 SP4   |
| <ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>                 | V2.3 / -   |
| Configuration control  |  |
| via dataset  | Yes  |
| Supply voltage   |  |
| Rated value (DC)   | 24 V   |
| permissible range, lower limit (DC)  | 19.2 V   |
| permissible range, upper limit (DC)  | 28.8 V   |
| Reverse polarity protection  | Yes  |
| Short-circuit protection   | Yes  |
| Mains buffering  |  |
| <ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>               | 10 ms  |
| Input current  |  |
| Current consumption (rated value)  | 450 mA   |
| Current consumption, max.  | 550 mA   |
| Inrush current, max.   | 3.7 A  |
| $I^2t$   | 0.09 A <sup>2</sup> ·s                           |
| Power loss   |  |
| Power loss, typ.   | 1.9 W  |
| Address area   |  |
| Address space per module   |  |
| <ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>                         | 256 byte; For input and output data respectively |
| Address space per station  |  |
| <ul style="list-style-type: none"> <li>Address space per station, max.</li> </ul>                        | 512 byte   |
| Hardware configuration   |  |
| Rack   |  |
| <ul style="list-style-type: none"> <li>Quantity of operable ET 200SP modules, max.</li> </ul>            | 32   |
| <ul style="list-style-type: none"> <li>Quantity of operable ET 200AL modules, max.</li> </ul>            | 16   |
| Submodules   |  |

|   |  |
|---|--|
| • Number of submodules per station, max.            | 256  |
| <b>Interfaces</b>                                   |  |
| Number of PROFINET interfaces                       | 1; 2 ports (switch)  |
| <b>1. Interface</b>                                 |  |
| <b>Interface types</b>                              |  |
| • RJ 45 (Ethernet)                                  | Yes  |
| • Number of ports                                   | 2  |
| • integrated switch                                 | Yes  |
| • BusAdapter (PROFINET)                             | Yes; compatible BusAdapters: BA 2x RJ45, BA 2x FC, BA 2x M12 |
| <b>Protocols</b>                                    |  |
| • PROFINET IO Device                                | Yes  |
| • Open IE communication                             | Yes  |
| • Media redundancy                                  | Yes; PROFINET MRP  |
| <b>PROFINET IO Device</b>                           |  |
| <b>Services</b>                                     |  |
| — IRT   | Yes; 250 µs to 4 ms in 125 µs frame                          |
| — PROFinergy  | Yes  |
| — Prioritized startup                               | Yes  |
| — Shared device                                     | Yes  |
| — Number of IO Controllers with shared device, max. | 2  |
| <b>Interface types</b>                              |  |
| <b>RJ 45 (Ethernet)</b>                             |  |
| • Transmission procedure                            | PROFINET with 100 Mbit/s full duplex (100BASE-TX)            |
| • 100 Mbps  | Yes  |
| • Autonegotiation                                   | Yes  |
| • Autocrossing                                      | Yes  |
| <b>Protocols</b>                                    |  |
| Modbus TCP  | No   |
| <b>Redundancy mode</b>                              |  |
| • PROFINET system redundancy (S2)                   | No   |
| <b>Media redundancy</b>                             |  |
| — MRP   | Yes  |
| — MRPD  | No   |
| <b>Open IE communication</b>                        |  |
| • TCP/IP  | Yes  |
| • SNMP  | Yes  |
| • LLDP  | Yes  |
| <b>Interrupts/diagnostics/status information</b>    |  |
| Status indicator                                    | Yes  |
| Alarms  | Yes  |
| Diagnostics function                                | Yes  |
| <b>Diagnostics indication LED</b>                   |  |
| • RUN LED   | Yes; green LED   |
| • ERROR LED   | Yes; red LED   |
| • MAINT LED   | Yes; Yellow LED  |
| • Monitoring of the supply voltage (PWR-LED)        | Yes; green PWR LED   |
| • Connection display LINK TX/RX                     | Yes; 2x green link LEDs on BusAdapter                        |
| <b>Potential separation</b>                         |  |
| between backplane bus and electronics               | No   |
| between PROFINET and all other circuits             | Yes; 1500 V AC (type test)                                   |
| between supply and all other circuits               | No   |
| <b>Permissible potential difference</b>             |  |
| between different circuits                          | Safety extra low voltage SELV                                |
| <b>Isolation</b>                                    |  |
| Isolation tested with                               | 707 V DC (type test)   |
| <b>Standards, approvals, certificates</b>           |  |
| Network loading class                               | 2  |
| Security level                                      | According to Security Level 1 Test Cases V1.1.1              |
| <b>Ambient conditions</b>                           |  |
| Ambient temperature during operation                |  |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul> | -30 °C; No condensation<br>60 °C<br>-30 °C; No condensation<br>50 °C   |
| <b>Altitude during operation relating to sea level</b>   |  |
| <ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>  | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| <b>connection method / header</b>  |  |
| <b>ET-Connection</b>   |  |
| <ul style="list-style-type: none"> <li>• via BU/BA Send</li> </ul>   | Yes; + 16 ET 200AL modules   |
| <b>Dimensions</b>  |  |
| Width  | 50 mm  |
| Height   | 117 mm   |
| Depth  | 74 mm  |
| <b>Weights</b>   |  |
| Weight, approx.  | 147 g; without BusAdapter  |