



LOGO! 24RCO (AC), LOGIC MODULE,
 PU/I/O: 24V AC/24V DC/RELAY, 8 DI/4 DO;
 W/O DISPLAY, MEMORY 400 BLOCKS,
 EXPANDABLE,
 ETHERNET BIULD IN WEB-SERVER,
 DATALOG STANDARD MICRO SD CARD FOR LOGO!
 SOFT COMFORT V8 PREVIOS PROJECT USABEL

| Installation type/mounting | |
|-------------------------------------|---|
| Mounting | on 35 mm DIN rail, 4 spacing units wide |
| Supply voltage | |
| 24 V DC | Yes |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| 24 V AC | Yes |
| Time of day | |
| Time switching clocks | |
| Number | 8 |
| Power reserve | 480 h |
| Digital inputs | |
| Number of digital inputs | 8 |
| Digital outputs | |
| Number of digital outputs | 4 ; Relays |
| Short-circuit protection | No ; external fusing necessary |
| Relay outputs | |
| Switching capacity of contacts | |

| | |
|---|---------|
| with inductive load, max. | 3 A |
| with resistive load, max. | 10 A |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| Emission of radio interference acc. to EN 55 011 (limit class B) | Yes |
| Degree and class of protection | |
| IP20 | Yes |
| Standards, approvals, certificates | |
| CSA approval | Yes |
| UL approval | Yes |
| FM approval | Yes |
| developed in accordance with IEC 61131 | Yes |
| acc. to VDE 0631 | Yes |
| Marine approval | |
| Marine approval | Yes |
| Ambient conditions | |
| Operating temperature | |
| min. | 0 °C |
| max. | 55 °C |
| Dimensions | |
| Width | 71.5 mm |
| Height | 90 mm |
| Depth | 58 mm |