



LOGO! AM2 AQ EXPAN. MODULE, PU: DC 24V, 0/4-20MA 2AQ, 0-10V FOR LOGO! 8

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>• 12 V DC</li> <li>• 24 V DC</li> </ul>	<p>No</p> <p>Yes</p>
Analog outputs	
Number of analog outputs	2
Output ranges, voltage	
<ul style="list-style-type: none"> <li>• 0 to 10 V</li> </ul>	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> <li>• Limit class B, for use in residential areas</li> </ul>	Yes
Degree and class of protection	
Degree of protection to EN 60529	
<ul style="list-style-type: none"> <li>• IP20</li> </ul>	Yes
Standards, approvals, certificates	
CSA approval	Yes
UL approval	Yes
FM approval	Yes
Developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	

- Marine approval

Yes

#### Ambient conditions

##### Ambient temperature in operation

- Min.
- max.

0 °C

55 °C

#### Dimensions

Width

35.5 mm

Height

90 mm

Depth

58 mm