



MATERIAL FACT SHEET

231506 FX3U-64MT/DSS

General Data

Product Hierarchy	IAD213
	Compact PLC
	FX3U
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

FA-COM PLC: Main Unit

Series	MELSEC-F SERIES
Type	FX3U
Power Supply (V)	24
Current Type	DC
Program Memory	64K STEPS
Program Memory Unit	RAM
Integrated Digital Inputs	32
Integrated Digital Outputs	32
Output Type	TRANSISTOR
Output Logic	SOURCE
Local I/O Points	256
Local + Remote I/O Points	384
Expandable	YES
Cycle Time LD (ns)	65
Cycle Time MOV (ns)	642
USB	OPTION
RS-422	1
Power Consumption (W)	40
Buffer Battery	YES
Protection Class	IP10
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

Product Dimensions & Weight

Width (mm)	220
Height (mm)	90
Depth (mm)	86
Weight (kg)	1

Logistic Dimensions & Gross Weight

Length (cm)	28,5
Width (cm)	12,0
Height (cm)	11,0
Gross Weight (kg)	1,156
Volume (cdm)	3,762

Stock Data

Planned Delivery Time (Days)	156
------------------------------	-----

Life Cycle

Sales Start	18.03.2010
Predecessor	206187 / FX3U-64MT/DSS

Additional Product Information

Binding Tariff Information	DEBTI-10854/21-1
BTI validity date	10.10.2024
Battery included	YES – CHECK SPARE PART LIST

Export Data

Commodity Code	85371091
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,KR,LR,NK,RINA
UKCA	COMPLIANT

Product Packaging

Cardboard (g)	198
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

Spare parts

Material	Description	Quantity	Unit
165286	FX3U-32BL	1	PC

Compatible products

Material	Description / Price List Text / Classification
31870	FX-20P-CADP GOT FX Series Adapter cable; 0.3 m Class 100100110: FA-COM PLC: Cable
45348	FX0N-65EC PLC, FX Series Connection Cable for Base and Extension units FX0N/FX2N, 0.65m Class 100100110: FA-COM PLC: Cable
70880	FX2N-CNV-BC PLC, FX2N Adapter for FX extension or special function modules Class 100100111: FA-COM PLC: Other Option
76094	FX-422CAB0 RS422 connection cable for FX0/0S/0N/2N Class 100100110: FA-COM PLC: Cable
159642	FX-232AWC-H RS-422/RS-232C converter to connect FX PLC and PC Class 100100111: FA-COM PLC: Other Option
165268	FX3U-7DM PLC, FX Series Display Unit Class 100100111: FA-COM PLC: Other Option
165278	FX3U-FLROM-16 PLC, FX3U Flash-RAM memory cassette; 16k steps PLC program Class 100100111: FA-COM PLC: Other Option
165279	FX3U-FLROM-64 PLC, FX3U Series Flash-RAM memory cassette; 64k steps PLC program Class 100100111: FA-COM PLC: Other Option

Material	Description / Price List Text / Classification
165280	FX3U-FLROM-64L PLC, FX3U Flash-RAM memory cassette; 64K steps PLC program; incl. copy function Class 100100111: FA-COM PLC: Other Option
165281	FX3U-232-BD PLC, FX3U RS232C Interface module; for MELSEC FX3U Class 100100107: FA-COM PLC: Serial Com Module
165282	FX3U-422-BD PLC, FX3U RS422 Interface module; for MELSEC FX3U Class 100100107: FA-COM PLC: Serial Com Module
165283	FX3U-485-BD PLC, FX3U RS485 Interface module, 1:n Multidrop, network expansion until 50 m Class 100100107: FA-COM PLC: Serial Com Module
165284	FX3U-USB-BD PLC, FX3U USB Interface module incl. USB cable (3m) Class 100100107: FA-COM PLC: Serial Com Module
165285	FX3U-CNV-BD PLC, FX3U Communication adapter for MELSEC FX3U ADP special function modules Class 100100111: FA-COM PLC: Other Option
165286	FX3U-32BL PLC, FX3U/C Battery Class 100100112: FA-COM PLC: Spare Part
165286	FX3U-32BL PLC, FX3U/C Battery Class 100101303: FA-OTHERS: Battery
165287	FX3U-7DM-HLD PLC, FX Series Panel Mounting Kit for FX3U-7DM incl. 1.5m cable Class 100100111: FA-COM PLC: Other Option
165288	FX-USB-AW PLC, Interface Converter USB/RS422 between PC and MELSEC PLC, 3 m Class 100100111: FA-COM PLC: Other Option
169507	FX3U-1PSU-5V PLC, FX Series Power supply module for 5V bus Class 100100111: FA-COM PLC: Other Option
206147	PSU 25 Power supply unit for 100-240V AC; Output 24V DC, DIN rail mounting Class 100100304: FA-HMI: Other Option
221271	FX-30P PLC, FX Series Hand-held programming unit Class 100100111: FA-COM PLC: Other Option
230104	FX3U-CF-ADP PLC, FX3U Data logger module; CF card slot; CSV file format Class 100100111: FA-COM PLC: Other Option
234630	GX Works2 V01-2L0C-E PLC Programming –S/W for MELSEC Q/L/F; USB; 2 PCs Class 100101201: FA-Software: Software PLC
234631	GX Works2 V01-5L0C-E SPS Programming-S/W for Melsec Q/L/F; USB; 5 PC's Class 100101201: FA-Software: Software PLC
237307	FX3U-8AV-BD PLC, FX3U analog setpoint adapter for 8 stpoints Class 100100111: FA-COM PLC: Other Option
244876	GX Works2 V01-2L0C-G PLC Programming S/W for MELSEC Q/L/F Series; German; USB; 2 PCs Class 100101201: FA-Software: Software PLC
244877	GX Works2 V01-5L0C-G PLC Programming –S/W for MELSEC Q/L/F; USB; 5 PCs Class 100101201: FA-Software: Software PLC
245565	FX3U-FLROM-1M SPS, FX3U(C) Memory cassette;1MB Class 100100111: FA-COM PLC: Other Option
248245	FX-20P-CAB0 PLC, FX Series Connection Cable with FX-10P-E/FX-20P-ESET0/FX-10DM-E,1,5m Class 100100110: FA-COM PLC: Cable
261190	FX3U-CNV-BD-BS Class 100100111: FA-COM PLC: Other Option
285598	FX0N-30EC PLC, FX Series Connection Cable for Base and Extension units FX0N/FX2N, 0.30m Class 100100110: FA-COM PLC: Cable

Material	Description / Price List Text / Classification
<u>286227</u>	iQ Works V02-2L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;2 PC's Class 100101201: FA-Software: Software PLC
<u>286228</u>	iQ Works V02-5L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;5 PC's Class 100101201: FA-Software: Software PLC
<u>303426</u>	iQ Works V02-15L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;15 PC's Class 100101201: FA-Software: Software PLC
<u>338821</u>	iQ Works V02-2L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;2 PC's Class 100101201: FA-Software: Software PLC
<u>339022</u>	iQ Works V02-5L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;5 PC's Class 100101201: FA-Software: Software PLC
<u>401853</u>	iQ Works V02-2L0C-IT iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;Italian;USB;2 PCs Class 100101201: FA-Software: Software PLC
<u>413493</u>	TRIO-PS-2G/1AC/24DC/5 Power supply unit for 100-240V AC; Output 24V DC / 5A, DIN rail mounting Class 100100304: FA-HMI: Other Option
<u>414700</u>	TRIO-PS-2G/1AC/24DC/3/C2LPS Power supply unit for 100-240V AC; Output 24V DC / 3A C2LPS, DIN rail mounting Class 100100304: FA-HMI: Other Option
<u>506252</u>	TRIO-PS-2G/1AC/24DC/10 Primary switched power supply; input: single phase, output: 24 VDC/10A, DIN rail Class 100100304: FA-HMI: Other Option
<u>506253</u>	TRIO-PS-2G/1AC/24DC/20 Primary switched power supply; input: single phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
<u>506254</u>	TRIO-PS-2G/3AC/24DC/20 Primary switched power supply; input: 3-phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
<u>506255</u>	TRIO-PS-2G/3AC/24DC/40 Primary switched power supply; input: 3-phase, output: 24 VDC/40A, DIN rail Class 100100304: FA-HMI: Other Option