



MATERIAL FACT SHEET

210085 FX3UC-96MT/D

General Data

Product Hierarchy	IAD213
	Compact PLC
	FX3U
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

FA-COM PLC: Main Unit

Series	MELSEC-F SERIES
Type	FX3UC
Power Supply (V)	24
Current Type	DC
Program Memory	64K STEPS
Program Memory Unit	EEPROM
Integrated Digital Inputs	48
Integrated Digital Outputs	48
Output Type	TRANSISTOR
Output Logic	SINK
Local I/O Points	256
Local + Remote I/O Points	384
Expandable	YES
Cycle Time LD (ns)	65
Cycle Time MOV (ns)	642
RS-422	1
Power Consumption (W)	14
Buffer Battery	YES
Protection Class	IP10
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

Product Dimensions & Weight

Width (mm)	85,4
Height (mm)	90
Depth (mm)	74
Weight (kg)	0,35

Logistic Dimensions & Gross Weight

Length (cm)	14,0
Width (cm)	11,0
Height (cm)	10,5
Gross Weight (kg)	0,447
Volume (cdm)	1,617

Stock Data

Planned Delivery Time (Days)	300
------------------------------	-----

Life Cycle

Sales Start	12.12.2007
Predecessor	212130 / FX2NC-96MT

Additional Product Information

Binding Tariff Information	DEBTI-10854/21-1
BTI validity date	10.10.2024
Battery included	YES – CHECK SPARE PART LIST

Export Data

Commodity Code	85371091
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,L,R,RINA
UKCA	COMPLIANT

Product Packaging

Cardboard (g)	75
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

Spare parts

Material	Description	Quantity	Unit
<u>165286</u>	FX3U-32BL	1	PC

Compatible products

Material	Description / Price List Text / Classification
<u>31870</u>	FX-20P-CADP GOT FX Series Adapter cable; 0.3 m Class 100100110: FA-COM PLC: Cable
<u>45348</u>	FX0N-65EC PLC, FX Series Connection Cable for Base and Extension units FX0N/FX2N, 0.65m Class 100100110: FA-COM PLC: Cable
<u>70880</u>	FX2N-CNV-BC PLC, FX2N Adapter for FX extension or special function modules Class 100100111: FA-COM PLC: Other Option
<u>76094</u>	FX-422CAB0 RS422 connection cable for FX0/0S/0N/2N Class 100100110: FA-COM PLC: Cable
<u>104508</u>	FX2NC-CNV-IF PLC, FX3UC Communication adapter for FX special function modules Class 100100111: FA-COM PLC: Other Option
<u>104509</u>	FX2NC-100MPCB PLC, FX Series Power supply cable for FX2NC base unit, 1 m Class 100100110: FA-COM PLC: Cable
<u>104510</u>	FX2NC-100BPCB Cable for 24V DC supply to input units Class 100100110: FA-COM PLC: Cable
<u>104511</u>	FX2NC-10BPCB1 Crossover cable for input units Class 100100110: FA-COM PLC: Cable
<u>125189</u>	FX-16E-TB/UL PLC, FX Series Extension terminal block 16 inputs/outputs Class 100100111: FA-COM PLC: Other Option

Material	Description / Price List Text / Classification
125584	FX-16E-150CAB PLC, FX Series Connecting cable 1,5 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable
128722	FX-16E-300CAB PLC, FX Series Connecting cable 3 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable
128723	FX-16E-500CAB-S PLC, FX Series Connecting cable 5 m FX2N-XXGM > External devices Class 100100110: FA-COM PLC: Cable
128724	FX-32E-TB/UL PLC, FX Series Extension terminal block 32 inputs/outputs Class 100100111: FA-COM PLC: Other Option
130451	FX-16E-500CAB PLC, FX Series Connecting cable 5 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable
134236	FX-16E-150CAB-R PLC, FX Series Extension terminal block cable, 1,5 m Class 100100110: FA-COM PLC: Cable
134265	FX-16E-300CAB-R PLC, FX Series Extension terminal block cable, 3 m Class 100100110: FA-COM PLC: Cable
134270	FX-16E-500CAB-R PLC, FX Series Extension terminal block cable, 5 m Class 100100110: FA-COM PLC: Cable
149021	TB-16EX-S PLC, FX Series Sensor terminal block for 16 inputs, screw connection Class 100100111: FA-COM PLC: Other Option
149038	TB-EX-CAB-1M PLC, FX Series Connection cable 1 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149039	TB-EX-CAB-3M PLC, FX Series Connection cable 3 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149040	TB-EX-CAB-5M PLC, FX Series Connection cable 5 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149148	TB-20-S PLC, FX Series Terminal block, 20 pin., screw connection Class 100100111: FA-COM PLC: Other Option
159642	FX-232AWC-H RS-422/RS-232C converter to connect FX PLC and PC Class 100100111: FA-COM PLC: Other Option
165278	FX3U-FLROM-16 PLC, FX3U Flash-RAM memory cassette; 16k steps PLC program Class 100100111: FA-COM PLC: Other Option
165279	FX3U-FLROM-64 PLC, FX3U Series Flash-RAM memory cassette; 64k steps PLC program Class 100100111: FA-COM PLC: Other Option
165280	FX3U-FLROM-64L PLC, FX3U Flash-RAM memory cassette; 64K steps PLC program; incl. copy function Class 100100111: FA-COM PLC: Other Option
165286	FX3U-32BL PLC, FX3U/C Battery Class 100100112: FA-COM PLC: Spare Part
165286	FX3U-32BL PLC, FX3U/C Battery Class 100101303: FA-OTHERS: Battery
165288	FX-USB-AW PLC, Interface Converter USB/RS422 between PC and MELSEC PLC, 3 m Class 100100111: FA-COM PLC: Other Option
210091	FX3UC-1PS-5V PLC, FX Series Power Supply module for 5V bus Class 100100111: FA-COM PLC: Other Option
221271	FX-30P PLC, FX Series Hand-held programming unit Class 100100111: FA-COM PLC: Other Option
230104	FX3U-CF-ADP PLC, FX3U Data logger module; CF card slot; CSV file format Class 100100111: FA-COM PLC: Other Option

Material	Description / Price List Text / Classification
234630	GX Works2 V01-2L0C-E PLC Programming –S/W for MELSEC Q/L/F; USB; 2 PCs Class 100101201: FA-Software: Software PLC
234631	GX Works2 V01-5L0C-E SPS Programming-S/W for Melsec Q/L/F;enl;USB;5 PC´s Class 100101201: FA-Software: Software PLC
244876	GX Works2 V01-2L0C-G PLC Programming S/W for MELSEC Q/L/F Series; German; USB; 2 PCs Class 100101201: FA-Software: Software PLC
244877	GX Works2 V01-5L0C-G PLC Programming –S/W for MELSEC Q/L/F; USB; 5 PCs Class 100101201: FA-Software: Software PLC
245091	FX2NC-CNV-IF-BS PLC, FX3UC Communication adapter for FX special function modules; coated Class 100100111: FA-COM PLC: Other Option
245565	FX3U-FLROM-1M SPS, FX3U(C) Memory cassette;1MB Class 100100111: FA-COM PLC: Other Option
248245	FX-20P-CAB0 PLC, FX Series Connection Cable with FX-10P-E/FX-20P-ESET0/FX-10DM-E,1,5m Class 100100110: FA-COM PLC: Cable
285598	FX0N-30EC PLC, FX Series Connection Cable for Base and Extension units FX0N/FX2N, 0.30m Class 100100110: FA-COM PLC: Cable
286227	iQ Works V02-2L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;enl;USB;2 PC´s Class 100101201: FA-Software: Software PLC
286228	iQ Works V02-5L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;enl;USB;5 PC´s Class 100101201: FA-Software: Software PLC
303426	iQ Works V02-15L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;enl;USB;15 PC´s Class 100101201: FA-Software: Software PLC
338821	iQ Works V02-2L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;2 PC´s Class 100101201: FA-Software: Software PLC
339022	iQ Works V02-5L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;5 PC´s Class 100101201: FA-Software: Software PLC
401853	iQ Works V02-2L0C-IT iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;Italian;USB;2 PCs Class 100101201: FA-Software: Software PLC
413493	TRIO-PS-2G/1AC/24DC/5 Power supply unit for 100-240V AC; Output 24V DC / 5A, DIN rail mounting Class 100100304: FA-HMI: Other Option
414700	TRIO-PS-2G/1AC/24DC/3/C2LPS Power supply unit for 100-240V AC; Output 24V DC / 3A C2LPS, DIN rail mounting Class 100100304: FA-HMI: Other Option
506252	TRIO-PS-2G/1AC/24DC/10 Primary switched power supply; input: single phase, output: 24 VDC/10A, DIN rail Class 100100304: FA-HMI: Other Option
506253	TRIO-PS-2G/1AC/24DC/20 Primary switched power supply; input: single phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
506254	TRIO-PS-2G/3AC/24DC/20 Primary switched power supply; input: 3-phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
506255	TRIO-PS-2G/3AC/24DC/40 Primary switched power supply; input: 3-phase, output: 24 VDC/40A, DIN rail Class 100100304: FA-HMI: Other Option
599623	FX2C-I/O-CON FX Series connector for flat cable; 20 pin; 1,27 pitch; AWG28; 10 pieces set Class 100100111: FA-COM PLC: Other Option
599624	FX2C-I/O-CON-S FX Series connector for loose wire; 20 pin; incl. cripm contacts; AWG22; 5 sets Class 100100111: FA-COM PLC: Other Option
599625	FX2C-I/O-CON-SA FX Series connector for loose wire; 20 pin; incl. cripm contacts; AWG20; 5 sets Class 100100111: FA-COM PLC: Other Option