

AFP7Y16R | FP7 Input and Output units



※Photo may vary from actual product.

RoHS compliant

Product Number	AFP7Y16R
Part Number	AFP7Y16R
Product	FP7 Input and Output Units
Details	Output units
Product name	FP7 Input and Output units

Spec Detail

As of September 04, 2023

Specifications and design of the products are subject to change without notice for the product improvement.

Item	Specifications
Product Number	AFP7Y16R
Part Number	AFP7Y16R
[[OUTPUT SPECIFICATIONS]]Insulation method	Relay insulation
[[OUTPUT SPECIFICATIONS]]Rated control capacity	2 A 250 V AC, 2 A 30 V DC
[[OUTPUT SPECIFICATIONS]]Min. load	1 mA 100 mV DC (resistive load)
[[OUTPUT SPECIFICATIONS]]Output type	-
[[OUTPUT SPECIFICATIONS]]Rated load voltage	-
[[OUTPUT SPECIFICATIONS]]Load voltage allowable range	-
[[OUTPUT SPECIFICATIONS]]Max. load current:0.3 A (Y0 to Y7)	-
[[OUTPUT SPECIFICATIONS]]Max. load current:0.1 A (other than that above)	-
[[OUTPUT SPECIFICATIONS]]Common restriction	5 A
[[OUTPUT SPECIFICATIONS]]Max. surge current	-
[[OUTPUT SPECIFICATIONS]]OFF state leakage current	-
[[OUTPUT SPECIFICATIONS]]ON state maximum voltage drop	-
[[OUTPUT SPECIFICATIONS]]Repose time:OFF→ON	10 ms approx.
[[OUTPUT SPECIFICATIONS]]Repose time:ON→OFF	8 ms approx.
[[OUTPUT SPECIFICATIONS]]Life time:Mechanical life	2 x 10 ⁷ operations or more
[[OUTPUT SPECIFICATIONS]]Life time:Electrical life	1 x 10 ⁵ operations or more

[[OUTPUT SPECIFICATIONS]]External power supply:Voltage	-
[[OUTPUT SPECIFICATIONS]]External power supply:Current (at 24 V)	-
[[OUTPUT SPECIFICATIONS]]Surge absorber	Snubber circuit (leakage current: 0.2 mA or less)
[[OUTPUT SPECIFICATIONS]]Relay socket	-
[[OUTPUT SPECIFICATIONS]]Short circuit protection	-
[[OUTPUT SPECIFICATIONS]]Output points per common	16 points/common
[[OUTPUT SPECIFICATIONS]]Operating mode indicator	16 points LED display (lights when ON)
[[OUTPUT SPECIFICATIONS]]External connection method	Terminal block (M3 screw)
[[COMMON GENERAL SPECIFICATIONS]]Ambient temperature	0 to +55 °C +32 to +131 °F, Storage: -40 to +70 °C -40 to +158 °F
[[COMMON GENERAL SPECIFICATIONS]]Ambient humidity	10 to 95 % RH (at +25 °C +77 °F, no condensation), Storage: 10 to 95 % RH (at +25 °C +77 °F, no condensation)
[[COMMON GENERAL SPECIFICATIONS]]Vibration resistance	5 to 8.4 Hz, single amplitude of 3.5 mm 0.138 in, 1 sweep/min. (IEC 61131-2) ; 8.4 to 150 Hz, constant acceleration of 9.8 m/s ² , 1 sweep/min. (IEC 61131-2), 10 times each in X, Y, and Z directions
[[COMMON GENERAL SPECIFICATIONS]]Shock resistance	147 m/s ² or more , 3 times each in X, Y, and Z directions (IEC61131-2)
[[COMMON GENERAL SPECIFICATIONS]]Noise immunity	1,000 V [p-p] with pulse width 50 ns and 1 micro s (using a noise simulator)
[[COMMON GENERAL SPECIFICATIONS]]Operating condition	Free from corrosive gasses and excessive dust
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Rated voltage range	-
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Current consumption	180 mA or less
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Net weight	180 g approx.

Accessories



Product Number **AFP7TER**

Part Number **AFP7TER**

Product name **FP7 Terminal block**